MAXIMIZE YOUR DISTANCE WITH CALLAWAY OPTIFIT ADJUSTABILITY



LOFT AND LIE ADJUSTABILITY INSTRUCTIONS:

The hosel consists of two cogs - an upper cog and a lower cog - that rotate independently to provide a total of 8 possible loft and lie combinations.

LOFT settings are designated as:

- "-1" Subtracts 1 degree from Stated Loft
- "S" = Stated loft (Loft stamped on Clubhead)
- "+1" Adds 1 degree to Stated Loft
- "+2" Adds 2 degrees to Stated Loft

LIE settings are designated as:

- "N" Neutral Setting
- "D" Draw Setting

ADJUSTING YOUR CLUB:

STEP 1 Select the desired loft by selecting one of the four choices **(S, -1, +1 or +2)** and lining it up with the two white "hash" marks on the top and bottom of the hosel assembly.

**Keep in mind, the loft selection could be located on either the upper or lower cog.





DRIVER - CURRENT - OPTIFIT 2

FAIRWAY/HYBRID - NEW - OPTIFIT 3

STEP 2 On the other cog, select Neutral or Draw by choosing "**N**" for Neutral or "**D**" for Draw. Position the "**N**" or "**D**" so that it sits between the "hash" marks and in line with the chosen Loft Selection. **Note: The "D" setting creates a more upright lie angle.



The new OptiFit 3 hosel is not backward compatible with previous versions of the OptiFit hosel. Using shafts with the older hosel could damage the hosel assembly.

www.callawaygolf.com/optifitinstructions To learn more about the adjustability features

